

MT502M49VH/AV/A

15/80 GHz 37/50 dBi 2 Ft Dish



Electrical				
Regulatory Compliance		ETSI EN 302 217-4-2 V2.1.1, FCC 47 CFR 101.115, RoHS, CE		
Frequency Range		14.4 – 15.35 GHz 71 – 76, 81 – 86 GHz		
Gain	Low Band	Mid Band	High Band	
14.4 – 15.35 GHz	36 dBi	36.5 dBi	37 dBi	
71 – 76/81- 86 GHz	50 dBi		51 dBi	
VSWR				
14.4 – 15.35 GHz	2.0 :1			
71 – 76/81- 86 GHz	1.5 :1			
3 dB Beam width				
14.4 – 15.35 GHz	2.5°			
71 – 76/81- 86 GHz	0.5°			
Polarization				
14.4 – 15.35 GHz	Single or Dual Pol (V + H)			
71 – 76/81- 86 GHz	Single or Dual Pol (V + H)			
Side Lobe Suppression				
14.4 – 15.35 GHz	ETSI Class 3			
71 – 76/81- 86 GHz	ETSI Class 3, FCC			
Cross Polarization				
14.4 – 15.35 GHz	ETSI Class 3			
71 – 76/81- 86 GHz	ETSI Class 3, FCC			
F/B Ratio				
14.4 – 15.35 GHz	ETSI Class 3	64 dB		
71 – 76/81- 86 GHz	ETSI Class 3, FCC	67 dB		
XPD				
14.4 – 15.35 GHz	ETSI Category 2	27 dB		
71 – 76/81- 86 GHz		30 dB		
Isolation				
WR62 to WR12	80 dB			
WR12 to WR62	25 dB			
Input Power	10 W (max)			
Mechanical				
Diameter	Ø 655 mm			
Depth	300 mm			
Weight	6.2 Kg max			
Interface				
14.4 – 15.35 GHz	WR62 or Circular			
71 – 76/81- 86 GHz	WR12 or Circular			
Radome	Polypropylene			
Environmental				
Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 68-2-1	72h	-55°C	
High Temperature	IEC 68-2-2	72 h	+71°C	
Temp. Cycling	IEC 68-2-14	1h	-45°C +70°C	3 Cycles
Vibration	IEC 60721-3-4	30 min/axis		Random 4M5
Shock Mechanical	IEC 60721-3-4			4M5
Humidity	ETSI EN300-2-4 T4.1E	144h		95%
Water Tightness	IEC 529			IP67 (for feed and radio interfaces)
Solar Radiation	ASTM G53	1000 h		
Salt Spray	IEC 68-2-11 Ka	500h		
Ice And Snow				25mm Radial
Wind Speed:	ETSI EN 302 085 V1.1.2			
Survival	Heavy Duty			252 Km/h
Operation	Heavy Duty			164 Km/h

Rev
THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE PROPRIETARY AND CONFIDENTIAL TO MTI. NO PERSON IS ALLOWED TO COPY REPRINT REPRODUCE OR PUBLISH ANY PART OF THIS DOCUMENT NOR DISCLOSE ITS CONTENTS TO OTHERS NOR MAKE ANY USE OF IT NOR ALLOW OR ASSIST OTHERS TO MAKE ANY USE OF IT, UNLESS BY THE PRIOR WRITTEN EXPRESS AUTHORIZATION OF MTI AND THEN ONLY TO THE EXTENT AUTHORIZED. (C) COPYRIGHT – MTI WIRELESS EDGE LTD.

MTI Wireless Edge Ltd. 11 Hamelacha St., Afek Industrial Park, Rosh Ha'ayin 48091 Israel

Tel: +972-3-9008900, Fax: +972-3-9008901

sales@mtiwe.com | www.mtiwe.com