

MT1380M50VH/AV/A

13/80 GHz 35/50 dBi 2 Ft Dish



Electrical				
Regulatory Compliance		ETSI EN 302 217-4 V2.1.1 (2017-05) FCC 47 CFR 101.115 RoHS, CE		
Frequency		12.2 – 13.25 GHz 71 – 76 GHz , 81 – 86 GHz		
Gain 12.2 – 13.25 GHz 71 – 76, 81 – 86 GHz		Low Band 35 dBi 50dBi	Mid. Band 35.4 dBi	High Band 35.7 dBi 51 dBi
VSWR 12.2 – 13.25 GHz 71 – 76, 81 – 86 GHz		1.5 : 1 1.5 : 1		
3 dB Beam width 12.2 – 13.25 GHz 71 – 76, 81 – 86 GHz		2.4° 0.5°		
Polarization 12.2 – 13.25 GHz 71 – 76, 81 – 86 GHz Side Lobe Suppression 12.2 – 13.25 GHz 71 – 76, 81 – 86 GHz		Single or Dual Pol (V + H) Single or Dual Pol (V + H)		
F/B Ratio 12.2 – 13.25 GHz 71 – 76, 81 – 86 GHz		ETSI Class 3 ETSI Class 3 , FCC		
XPD 12.2 – 13.25 GHz 71 – 76, 81 – 86 GHz		55 dB 67 dB		
Isolation WR62 to WR12 @ Low Range WR12 to WR62 @ High Range		ETSI Category 2 35 dB 25 dB		
Input Power		80 dB 25 dB		
10 W				
Mechanical				
Dimensions		Ø655 mm max		
Depth		300 mm		
Weight		8 Kg (max)		
Interface 12.2 – 13.25 GHz 71 – 76, 81 – 86 GHz		WR62 or Circular WR12 or Circular		
Radome		Plastic		
Mounting Kit		MT-120032/A, weight 4kg max.		
Environmental				
Test	Standard	Duration	Temperature	Notes
Low Temperature	IEC 60068-2-1	72 h	-55°C	
High Temperature	IEC 60068-2-2	72 h	+71°C	
Temp. Cycling	IEC 60068-2-14	1 h	-45°C +70°C	3 Cycles
Vibration	IEC 60721-3-4	30 min/axis		Random4M5
Shock Mechanical	IEC 60721-3-4			4M5
Humidity	EN300 019-2-4 T4.1E	144 h		95%
Water Tightness	IEC 60529			IP67*
Solar Radiation	ASTM G53	1000 h		
Salt Spray	IEC 60068-2-11 Ka	500 h		
Ice And Snow	-			25mm Radial
Wind Speed	ETSI EN 302 085 V1.1.2			252 Km/h
Survival	HEAVY DUTY			164 Km/h
Operation	HEAVY DUTY			

* For the feed & interface to the radio (when radio installed on antenna).

Rev

THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE PROPRIETARY AND CONFIDENTIAL TO MTI. NO PERSON IS ALLOWED TO COPY REPRINT REPRODUCE OR PUBLISH ANY PART OF THIS DOCUMENT NOR DISCLOSE ITS CONTENTS TO OTHERS NOR MAKE ANY USE OF IT NOR ALLOW OR ASSIST OTHERS TO MAKE ANY USE OF IT, UNLESS BY THE PRIOR WRITTEN EXPRESS AUTHORIZATION OF MTI AND THEN ONLY TO THE EXTENT AUTHORIZED.

(C) COPYRIGHT – MTI WIRELESS EDGE LTD.

MTI Wireless Edge Ltd. 11 Hamelacha St., Afek Industrial Park, Rosh Ha'ayin 48091 Israel

Tel: +972-3-9008900, Fax: +972-3-9008901

sales@mtiwe.com | www.mtiwe.com